

DOUBLE COMPRESSION EXPLOSION-PROOF CABLE GLAND:

Application

- Hazardous area

Material:

Brass, Stainless steel 304,316

Seal:Silicon rubber



Properties

- When installing cable,it will flameproof diaphragm seal in inner sheath
- With quick installation,safety,reliability and other characteristics of good protection
- It is suitable for clamping and fixing various types of armored cables.

Technical data

Protection class:IP66

Temperature range:-40°C up to +100°C



Product Code	Thread AG		Outer Diameter of Cable (mm)		Thread length L1(mm)	Length L (mm)
			Outlet A	Incoming Line B		
JX-6-EX-15A	M16*1.5	-	5-8	7-15	15	67
JX-6-EX-15B	M20*1.5	NPT1/2	5-12	8-15	15	67
JX-6-EX-20	M25*1.5	NPT3/4	8-17	11-20	15	71
JX-6-EX-27	M32*1.5	NPT1	11-22	14-27	17	76
JX-6-EX-33	M40*1.5	NPT1 1/4	14-28	19-33	17	76
JX-6-EX-40	M50*1.5	NPT1 1/2	16-33	22-40	17	94
JX-6-EX-50	M63*1.5	NPT2	29-43	29-50	17	98
JX-6-EX-63	M75*1.5	NPT2 1/2	38-57	35-63	17	112
JX-6-EX-77A	M85*1.5	NPT3S	38-72	41-77	18	114
JX-6-EX-77B	M90*1.5	NPT3	38-72	41-77	18	126
JX-6-EX-83	M100*1.5	NPT4S	48-83	55-90	18	126
JX-6-EX-94	M110*1.5	NPT4	48-94	61-104	18	128